### Mactenn Systems Limited

One Bull Lane, Acton, Sudbury, Suffolk CO10 0BD UK Tel: +44 1787 882 422 Fax: +44 1787 882 433 sales@mactenn.com

# Macawber Engineering Systems

India Private Ltd. 131 Hindustan Kohinoor Complex, L.B.S. Marg, Vikhroll (West) Mumbai – 400 083 INDIA Tel : +91 22 6796 9655 Fax: +91 22 2579 4624 sales@macawberindia pet

### Macawber Japan

3-11-1, Shinmachi, Nishi-ku Osaka 550 JAPAN Tel : +81 66 538 9190 Fax: +81 66 533 2979 taiheisn@pearl.ocn.ne.ip

## Macawber China Wusi Farm, Feng Xiai Shanghai 201422

CHINA Tel : +86 21 571 60541 Fax: +86 21 571 66248 macawber@macawber.com.c

### Macawber Do Brazil (Lisencee)

Av. Dr. Pedro Lessa, 1.447 – Conj Santos – Sao Paulo BRAZIL – CEP 11025-001 Tel : +55 13 3227 3380 Fax: +55 13 3271 3140 pdl@pdl.com.br

# Mactenn

### Mactenn Systems Limited

One Bull Lane, Acton, Sudbury, Suffolk CO10 0BD Tel: +44 1787 882 422 Fax: +44 1787 882 433

A Macawber Group Company

ADVANCED PNEUMATIC CONVEYING SYSTEMS CONTROLLED RATE INJECTION SYSTEMS

Your Local Distributor:

C E Product Safety requirements satisfy the Directives of the European Commission.

Macawber Engineering, Inc

1829 Clydesdale Street

Tel: +1 865 984 5286

# Mactenn Systems



ISO 9001



# Ash Conveying Systems

Pneumatic Dense-Phase Ash Conveying Systems

# Mactenn

Multiple pick-up (feed) points on a single pipeline
Low profile equipment – excellent for retrofitting
Low power cost per ton transferred
Maintenance free equipment – no continuously moving parts
Very low material transfer velocity-schedule 40 pipeline
Worldwide experience since 1974
Worldwide technical support
ISO 9001



# Low velocity fly ash handling

- 1. A well-proven method of transferring ash through standard pipelines at low velocity using small equipment that is virtually maintenance free. Continuous development since 1974 with concentrated specialisation ensures highest efficiency and operating reliability.
- 2. Experience in this specialised field is vital to success. Every ash type and combustion type has been handled by the Mactenn dense-phase technology.
- 3. The Multiashflo® operating sequence is very simple and relaxed. The small cast iron vessels do not require a vent valve, a level probe or a discharge valve. Each cycle clears away deposited ash from the feed hopper leaving them normally empty.
- 4. Each line of Multiashflos® on each ESP field, economiser or bag house cycle simultaneously to transfer the ash through a common pipeline. Diverter valves for each feed point are not required and system controls are equally simple.
- 5. Typically, a major coal fired utility of 2 x 300 Mwatt units using low quality coal with high ash content requires 46 tons/hour design rate over 350 metres from ESP units and handling high temperature ash at 350°C from the economiser.



# How does Mactenn Technology **Compare with Old Technology?**

The following table compares Mactenn's low-velocity, dense-phase Multiashflo® technology with the traditional (old) technologies of positive pressure, dilute-phase conveying and vacuum dilute-phase conveying. The example is for a typical conveying distance of 100 m (330 ft.).

## **Dimensions**

Characteristic	Positive Pressure Dilute Phase	Vacuum Dilute Phase Dense	MULTIASHFLO® Phase
Material-to-air Ratio	13	8	90
Average Material Velocity	78 m/s (60 f/s)	20 m/s (65 f/s)	4 m/s (13 f/s)
Energy Consumption kw per ton conveyed	110 kw	135 kw	75 kw
Pipewear	High	High	Low
ESP Hoppers Always Empty	No	No	Yes
Pipeline Material	Schedule 80 carbon steel or chrome cast iron	Chrome cast iron	Schedule 40 carbon steel

# How does Mactenn Compare with other Dense-phase Systems?

The typical old style dense-phase systems comprise large vessels with complex pipeline arrangements involving tee connections and discharge valves. The Mactenn Multiashflo® system is compact, easy to install, and uses a single in-line pipeline arrangement that eliminates tee connections and discharge valves. In addition, the Multiashflo® system does not require level probes, vent valves or air inlet valves to each vessel. The following comparison is a scaled size view.





.4 METERS





# 1. Dry Bottom Ash Handling

This is a proven development of the Multiashflo® working in conjunction with an ash crusher at each outlet. Crushed bottom ash is conveyed away through schedule 40 pipeline to storage.

# 2. From Wet to Dry

The elimination of water from bottom ash handling has many economic benefits. Additionally the problems of lagoon water quality control, space requirements and general maintenance requirements are avoided.

# 3. Operating Sequence

Each bottom ash outlet operates independently but conveys the ash through a common pipeline. The ash level inside the base of the boiler is signalled by a high temperature lazer probe to release accumulated bottom ash through special cooling dump doors. The clinker enters the ash crusher to be reduced in size for the Multiashflo® to convey the particles to storage.

The accumulated clinker ash is cooled continuously by part of the total combustion air passing through the porous deck of the ash dump doors. Heat gain to this part of the combustion air assists boiler efficiency.

The ash crusher control incorporates an auto reversing drive automatically applied in the event of crusher overload due to foreign material entering the clinker crusher. This function is displayed at central control with visual and audio alarms.

The ash conveying sequence control arrangement includes a fault diagnostic facility. An audio alarm and visual display describes a fault condition, which may be easily remedied with operator friendly intervention at the system control facia.



# The Inflatek® Valve

 The Inflatek® Valve was introduced and patented in 1978 for the sole purpose of providing long life and reliability when handling hot and abrasive materials.
 The unique inflatable seal traps abrasive particles on closing preventing their movement under the effect of the pressure differential. This action ensures wear resistance from particles, operating reliability and valve performance.

2. Continuous development over the years with additional patents and innovations has developed the market for the valve to many applications. In addition the valve is widely used to retrofit ash valves requiring high maintenance or frequent replacement.

3. The operating sequence of the Inflatek® Valve is very simple and effective; The spherical component rotates 90 to pass through a static or moving column of abrasive ash to the closed position where an inflatable seal is pressurised to entrap particles and prevent their movement. The inflatable seal reliably achieves a pressure differential of 7 barg at a high temperature.

4. The standard size range is 50mm to 400mm and 300°C with inline configuration for pipeline service or bulkhead configuration for pressure vessel inlet. Special Inflatek® Valves are available to 750mm and 43 barg with a range of materials of construction.

Inflatek® Valve Closure and Seal comparison with other valve types			
Function:	Knife Gate Valve	Butterfly Valve	E
Closing member away from material flow	YES	NO	١
<b>A 1 1 1</b>			

Close and seal on column of material	NO	NO	N
jamming on column of material	NO	NO	N

### Inflatek® Valve Pressure Comparison with other valve types

	Seal Bubble Tight to:	Knife Gate Valve	Butterfly Valve	Ball Valve	Inflatek® Valve
	14.5 psi (1 barg)	NO	NO	Maybe	YES
	100 psi (7 barg)	NO	NO	NO	YES
	623.5 psi (43 barg)	NO	NO	NO	YES
	Combined Pressure and Vacuum	NO	NO	Maybe	YES
~					

l ve	Inflatek® Valve
6	YES
	YES
	YES
	YES



5





# **Specialised Applications**

In addition to ash conveying systems, Mactenn has a range of equipment for special applications such as FBC bed drains, pressure let down systems, long distance conveying and ash re-injection.

# Ash Re-injection System

Mactenn can provide a range of ash re-injection systems. The Minimaxflo® is ideal for returning carbon-rich ash back into the combustion process.

# Long Distance Ash Conveying

Λ

Mactenn provides a range of technologies for conveying ash over distances up to 2000 m (6500 ft). These technologies include the Maxflo®, Variflow® and Macpump® dense-phase systems.

The Macpump® can convey at rates as high as 300 tph.





A high-temperature, dust tights clam shell type cut-off valve capable of up to 800°C operation.

# < Pressure Let-down Systems

Many combustion systems such as gasifiers, circulating fluid bed combusters and combined cycle systems operate at high pressures - often as high as 40 barg.

Mactenn Inflatek® Valve technology can provide means of transferring hot materials from high to low pressure environments.

Combined systems for pressure reduction and conveying are also available.

# **Application Examples**

Examples of the Multiashflo® ash handling process are well known throughout the world. They are used with all types of coal fired boiler and alternative fuels such as biomass, sewage sludge, garbage and medical waste.

1. Cottam Power Station UK. 4 x 500 Mwatt first fields ESP fly ash systems each comprising 9 x fly ash feed points on a single pipeline handling 28 tons/hour for 280 to 350 metres.

**2. London Waste UK**. 5 x 50 Mwatt ESP units handling domestic waste biomass fuel ash. Retrofit of dilute-phase ash handling system. handling 8 tons/hour for each system for 260 metres.

3. South Carolina Electric and Gas. USA. Retrofit of all ash handling and storage systems for 2 x 130 Mwatt boilers including bottom ash, fly ash, pyrites, back pass and air heater ash positions.

4. Liaoning Power Plant, China. Two new 300 Mwatt coal fired boilers for ESP fly ash and economiser fly ash. Design rate 46 tons/hour 360 metres.

5. Montenay Waste-to-Energy Plant, Panama City, Florida. USA. Handling lime-rich ash from garbage incineration with FGD treatment. Two streams, each stream conveying 2.5 tons/hour from Air Heater, FGD and Baghouse over 80 metres.

6. Shanghai Coke and Chemical Plant. China. High temperature ash from 8 gasifiers at 2 barg. Continuous pressure let down and dense-phase conveying at 350°C to storage. A total of 32 high temperature and high pressure let down/conveying systems.

7. Fibrothetford. UK. A comprehensive set of systems to handle ash from chicken litter biomass fuel. Bag house ash is heavily lime rich providing important variations to fly ash characteristics.

**8. Koblitz Energy, Brazil**. A waste to energy plant handling rice hulls fly ash. Four Multiashflos® transferring fly ash from a baghouse to a silo at 10 tons/hour over 250 metres.

9. City of Paulo Alto, USA. Sludge incineration plant handling sewage sludge ash at 18 tons/hour 180 metres in a 100mm pipeline with Multiashflos® conveying the ash to a storage silo and from there to a load out bin.

10. Alabama Power, Birmingham USA. Coal fired utility handling bottom ash and fly ash. Fifteen Model 1.5/8 Multiashflos® and seven with ash crushers. All ash is being transferred to a storage silo.

**11. Agrilectric, Lake Charles, USA**. Waste to energy plant handling rice hulls ash. Ten x 1.5/8 Multiashflos® operating on a 100mm pipeline conveying fly ash from baghouses and mechanical collectors to a silo.

**12. Mitsubisha, Japan**. Fly Ash transfer through a 250mm pipeline over 250 metres at 30 tons/hour.

13. Fiddlers Ferry Power Station, UK. Fly Ash transfer through a 300mm pipeline over 170 metres at 120 tons/hour.





7